MS103

Speaker diameter: 30 mm. Maximum input power: 100 mW. Impedance: 32 ohms at 1 kHz. Frequency response: 100 – 15,000 Hz. Omnidirectional condenser microphone.

Microphone	Yes
Volume control	Yes
Fixation	Tiara
Sound	Stereo
Frequency response (KHz)	100-15
Magnetic shield	Yes
Connection	Jack
Recommended use	Videoconferencing / Music / Gaming
Noise cancellation (micro)	Yes

Technical Information

Technical specifications:

Microphone:

Impedance: Low

Frequency Range: 20-16 kHz

Sensitivity: -62 dB+/- 3 dB

Length of cord: 1,8 m+/- 3 %

Headphone:

Impedance: 32 Ohms/l Khz

Frequency Range: 20-20 kHz

Sensitivity: 101 dB+/- 4 dB

Length of cord: 1,8 m+/- 3 %

Package contents:

MS103

Warranty card

Shipping Information

	Contains
Unity	1
Intermediate box	18
Export carton	36
Pallet	540

System Requirements

Stereo sound card

	Unity	Intermediate box	Export carton
EAN	8436001280455	8436001302805	8436001280707
Weight	0.11	2.3	5.3
Widht	0.165	0.42	0.435
Depth	0.053	0.28	0.3
Height	0.225	0.18	0.39
Warranty	5 years		

ID de FCC/FC			